VACUUM PACKING MACHINE SU-420GP 230/50-60/1 AUS

Tabletop model. 20 m³/h. 420 mm.



P/N 1140729



SALES DESCRIPTION

420 mm. sealing bar. 20 m³/h Busch vacuum pump. Vacuum controlled by sensor.

- ✓ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- √ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- √ "Pause" button.
- √ Phased vacuum programme.
- Detection of the evaporation of liquids.
- ✓ Double seal.
- √ Cordless sealing bar.
- ✓ Progressive decompression.
- √ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

INCLUDES

- √ Filling plate
- √ Inert gas flush
- Bluetooth connectivity
- ✓ Printer connection

SPECIFICATIONS

Pump capacity: 20 m3/h Pump capacity (60 Hz): 24 m3/h

Bar length: 420 mm Total loading: 750 W

Vacuum pressure (maximum): 2 mbar

Electrical supply: 230 V / 50-60 Hz / 1 ~ (5.5 A)

Internal dimensions

- √ Width: 430 mm
- ✓ Depth: 415 mm
- √ Height: 180 mm

External dimensions (WxDxH)

- √ Width: 484 mm
- ✓ Depth: 529 mm
- √ Height: 448 mm

Net weight: 56.7 Kg

Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

Crated dimensions

600 x 600 x 610 mm Gross weight: 62.7 Kg.

Accessories

- Bag cutting kits
- □ Filling plates
- Liquid insert plates
- Vac-norm external vacuum kits
- Vac-norm containers
- ☐ Smooth bags for vacuum packing
- □ Trolley for vacuum packing machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB Desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB





20720 Azkoitia, Spain



sales@sammic.com



Project	Date
Item	Qty