



One Solid Door Underbench GN1/1 Freezer

Model ID: PG11.UBF.1.SD

A chef's precision is crafted into every detail with the ProSpec. Setting the new benchmark for commercial refrigeration, including a sleek, clean aesthetic, full configurability, high-spec performance and integrated food safety data collection. Mould the ProSpec to work for you. Mix and match your desired number of bays, doors, drawers or both. Available in left or right hand services.



FEATURES & BENEFITS

- 2 Drawers per Door;#3 Drawers per Door;#Extra Shelf & Slides;#Punched S/S Shelves (per cabinet)
- SKOPE-connect™: control temperature from your smartphone with easy pre-sets and food safety security features

SPECIFICATIONS

- Dimensions: 835 W x 700 D x 850 (standard castors), 860 to 900 (legs), 720 (plinth mount) H (mm)
- Doors: 1
- Door Type: Solid
- Shelves: Two 304 stainless steel wire shelves 2 x shelf (330W x 550D)
- Material: 304 AISI stainless steel
- Gross Volume (Litres): 126
- Total Floor Area (m²): 0.58
- Weight (kg): 85
- Refrigeration Unit: Self-Contained
- Temperature Range: -21 to -18 (adjustable* from -26 to -12)
- Max Ambient Temperature: 40
- Refrigerant: R290/97 g
- GEMS Class: 5L1
- GEMS Energy Consumption (kWh/24h): 3.39 kWh/24 h
- Annual Running Costs: \$371 (@ \$0.30/kWh)
- kW: .86
- Current Draw (Amps): 3.6
- Interior Lighting: 1 x 400 mm, 4W LED light (door-activated)
- Controller: SCS Connect (SKOPE-connect™ compatible)
- Refrigeration System: Removable cartridge
- Power Cord: 2 m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 volts a.c., 50 Hz, single phase supply

OPTIONS